

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL AUTO PRIME FE 0W-30

Full Synthetic Automotive Engine Oil

January 10, 2025 (Ver.5243-01)

Viscosity

- 0W-30

Specifications:

- ACEA C2

Approvals:

- -

Recommendations:

- -

	PN	Variant
5243 Family	5243005	5L
	5243010	10L
	5243020	20L
	5243200	200L

Features & Benefits

- Ultra high-performance and extreme fuel economy engine oil, especially developed for modern Ford diesel engines.
- Optimum wear protection.
- Outstanding cold-start properties and low oil consumption.
- Suitable for diesel engines.
- 5L, 10L, 20L and 200L variants available (Note: Not all variants are available through all Bapcor Business Units).

Typical Characteristics

Property	Test Method	Value	Unit
Density @ 15 °C	DIN 51 757	0.843	g/ml
Flash Point, CoC	DIN ISO 2592	228	°C
Pour Point	DIN ISO 3016	-45	°C
Kinematic Viscosity @ 40 °C	DIN 51 562-1	45.8	mm ² /s
Kinematic Viscosity @ 100 °C	DIN 51 562-1	9.6	mm ² /s
Viscosity Index	DIN ISO 2909	201	-