

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL AUTO PLUS F A5/B5

Semi Synthetic Automotive Engine Oil

January 10, 2025 (Ver.5247-01)

Viscosity

- 5W-30

Specifications:

- API SL
- ACEA A5/B5

Approvals:

- -

Recommendations:

- -

	PN	Variant
5247 Family	5247005	5L
	5247010	10L
	5247020	20L
	5247200	200L

Features & Benefits

- Highly energy conserving multigrade passenger car engine oil suitable for Ford diesel and gasoline engines.
- High thermal and oxidative stability.
- Sludge protection.
- Excellent wear protection.
- 5L, 10L, 20L and 200L variants available (Note: Not all variants are available through all Bapcor Business Units).

Typical Characteristics

Property	Test Method	Value	Unit
Density @ 15°C	DIN 51757	0.854	g/ml
Colour	DIN ISO 2049	3	ASTM
Flash Point COC	DIN ISO 2592	224	°C
Dynamic Viscosity at -30°C	DIN 51398	4750	mPas
Dynamic Viscosity at 150 °C	CEC L-036-90	3,0	mPas
Kinematic Viscosity @ 40 °C	DIN 51562-1	55,2	mm²/s
Kinematic Viscosity @ 100 °C	DIN 51562-1	9.95	mm²/s