

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL AUTO PRIME MULTI 5W-30

Full Synthetic Automotive Engine Oil

January 17, 2025 (Ver.5250-01)

Viscosity

- 5W-30

Specifications:

- API SP
- ACEA C2/C3

Approvals:

- MB-APPROVAL 229.51/52/31

Recommendations:

- BMW LONGLIFE-04
- OPEL OV 040 1547
- CHRYSLER MS-11106
- FIAT 9.55535-S1/-S3
- GM-LL-A/B-025
- IVECO 18-1811 CLASSE SC1
- VW 505 00/505 0

5250 Family	PN	Variant
	5250005	5L
	5250010	10L
	5250020	20L
	5250200	200L

Features & Benefits

- Offers extreme fuel-economy with optimum cold start ability and outstanding performance reserved for modern passenger cars and light commercial vehicles with or without extended service intervals.
- Excellent fuel efficiency.
- Suitable for petrol and diesel engines.
- Recommended for European and Japanese vehicles.
- 5L, 10L, 20L and 200L variants available (Note: Not all variants are available through all Bapcor Business Units).

Typical Characteristics

Property	Test Method	Value	Unit
Density @ 15 Deg C	DIN 51757	0.85	kg/L
High Temperature High Shear (HTHS)	ASTM D4683	> 2.9	-
Kinematic Viscosity @ 100 Deg C	ASTM D445	11.5 typ.	cSt
Viscosity Index	ASTM D2270	> 160	-

Superiol.com.au

Superiol.co.nz