

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL AUTO PRIME A3/B4 5W-40

Full Synthetic Automotive Engine Oil

January 22, 2025 (Ver.5254-01)

Viscosity

- 5W-40

Specifications:

- API SN
- ACEA A3/B4

Approvals:

- MERCEDES BENZ
APPROVAL 226.5 /
229.5

Recommendations:

- PORSCHE A40
- PSA B71 2296
- RENAULT RN0700 /
RN0710
- VW 502 00 / 505 00
- BMW LONGLIFE-01

5254 Family	PN	Variant
	5254005	5L

Features & Benefits

- High performance engine oil for high performance engines.
- Thermally stable to minimize engine wear and can be used for extended drain intervals.
- Enhanced protection for high-performance engines.
- Suitable for European models.
- Compatible with both Petrol & Diesel engines.
- 5L variant available (Note: Not all variants are available through all Bapcor Business Units).

Typical Characteristics

Property	Test Method	Value	Unit
Density @ 15°C	DIN 51 757	852	kg/m3
Colour	DIN ISO 2049	2.5	ASTM
Flashpoint (COC)	DIN ISO 2592	225	°C
Dynamic Viscosity	DIN 51398	6000 (-30°C)	mPas
Kinematic viscosity at 40°C	DIN 51 562-1	82.8	mm2/sec
Kinematic viscosity at 100°C	DIN 51 562-1	13.8	mm2/sec
Viscosity Index	DIN ISO 2909	171	-