

# SUPERIOL

## PRODUCT DATA SHEET



### SUPERIOL HAUL CI-4 15W-40

#### Mineral Engine Oil

January 24, 2025 (Ver.5259-01)

#### Viscosity

- 15W-40

#### Specifications:

- API CI-4/SL
- ACEA E7

#### Approvals:

- -

#### Recommendations:

- ALLISON C-4
- CAT TO-2
- CASE MS 1121
- CUMMINS CES 20071/2
- IVECO 18-1804 CLASSE T2 E7
- NH 330H

|                        | PN      | Variant |
|------------------------|---------|---------|
| <b>5259<br/>Family</b> | 5259010 | 10L     |
|                        | 5259020 | 20L     |
|                        | 5259200 | 200L    |

#### Features & Benefits

- Ultra high-performance engine oil for a variety of diesel and gasoline engines.
- Excellent protection against wear and corrosion.
- Sludge and adhesions prevention.
- Heavy duty DPF compatible.
- Specially formulated for highly loaded commercial vehicle diesel engines.
- 10L, 20L and 200L variants available (Note: Not all variants are available through all Bapcor Business Units).

#### Typical Characteristics

| Property                     | Test Method  | Value  | Unit               |
|------------------------------|--------------|--------|--------------------|
| Density @ 15 °C              | DIN 51757    | 0.879  | g/ml               |
| SAE Grade                    | SAE J300     | 15W-40 | -                  |
| Kinematic Viscosity @ 40 °C  | DIN 51562-1  | 114.9  | mm <sup>2</sup> /s |
| Kinematic Viscosity @ 100 °C | DIN 51562-1  | 14.9   | mm <sup>2</sup> /s |
| Viscosity Index              | DIN ISO 2909 | 135    | -                  |
| HTHS                         | CEC L-036-90 | ≥3.5   | mPa*s              |
| Pour Point                   | DIN ISO 3016 | -33    | °C                 |
| Sulphated ash                | ASTM D874    | ≤ 2.0  | % m/m              |