

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL HAUL CJ-4/CK-4 15W-40

Mineral Engine Oil

January 23, 2025 (Ver.5260-01)

Viscosity

- 15W-40

Specifications:

- ACEA E9 E11
- API CJ-4/CK-4/SN

Approvals:

- MERCEDES BENZ APPROVAL 228.31

Recommendations:

- CAT ECF-3
- JASO DH-2
- CUMMINS CES 20086
- DETROIT DIESEL 93K222
- DEUTZ DQC III-10 LA
- FORD M2C171-F1
- MACK EOS 4.5
- MAN M 3775
- MTU DDC TYPE 2.1
- RENAULT RLD-3
- VOLVO VDS-4.5
- ALLISON TES-439 (439-34872020)
- MAN M 3575
- RENAULT RLD-4

Features & Benefits

- Premium-performance, fuel-economy engine oil for a wide range of commercial vehicle diesel engines.
- Specially developed for vehicles with extended service intervals, exhaust after-treatment systems and turbochargers.
- EGR and SCR compatible. Heavy Duty DPF compatible.
- 5L, 10L, 20L, 200L and 1000L (IBC) variants available
(Note: Not all variants are available through all Bapcor Business Units).

Typical Characteristics

Property	Test Method	Value	Unit
Density @ 15 °C	DIN 51757	0.872	g/ml
SAE grade	SAE J300	15W-40	-
Kinematic Viscosity @ 40 °C	ASTM D445	108	cSt
Kinematic Viscosity @ 100 °C	ASTM D445	14.4	cSt
Viscosity Index	ASTM D 2270	136	-
HTHS	CEC L-036-90	≥ 3.5	mPa*s
Pour Point	DIN ISO 3016	-39	°C
Sulphated Ash	DIN 51575	1	%w/w

5260 Family			
PN	Variant	PN	Variant
5260005	5L	5260200	200L
5260020	20L	52601000	1000L (IBC)

Superiol.com.au

Superiol.co.nz