

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL HAUL CJ-4 15W-40

Mineral Engine Oil

January 23, 2025 (Ver.5261-01)

Viscosity

- 15W-40

Specifications:

- ACEA E9
- API CJ-4/SM

Approvals:

- MERCEDES BENZ
APPROVAL 228.31

Recommendations:

- CUMMINS CES 20086
- DETROIT DIESEL
93K222
- DEUTZ DQC III-10 LA
- MAN M 3575
- MTU DDC TYPE 2.1
- RENAULT RLD-3
- VOLVO VDS-4.5

5261 Family	PN	Variant
	5261005	5L
	5261020	20L
	5261200	200L
	52611000	1000L (IBC)

Features & Benefits

- Revolutionary engine oil specially formulated for commercial diesel vehicles.
- Delivers exceptional performance on engine durability in highly stressed commercial vehicle engines.
- Combined advanced additive technology with a cutting-edge base oil matrix with superior oxidation stability.
- EGR and SCR compatible.
- Heavy Duty DPF compatible.
- 5L, 10L, 20L, 200L and 1000L (IBC) variants available
(Note: Not all variants are available through all Bapcor Business Units).

Typical Characteristics

Property	Test Method	Value	Unit
Density @ 15 °C	DIN 51757	0.872	g/ml
SAE grade	SAE J300	15W-40	-
Kinematic Viscosity @ 40 °C	ASTM D445	108	cSt
Kinematic Viscosity @ 100 °C	ASTM D445	14.4	cSt
Viscosity Index	ASTM D 2270	136	-
HTHS	CEC L-036-90	≥ 3.5	mPa*s
Pour Point	DIN ISO 3016	-39	°C
Sulphated Ash	DIN 51575	1	%w/w

Superiol.com.au

Superiol.co.nz