

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL AUTO SP/CF 15W-40

Mineral Automotive Engine Oil

January 23, 2025 (Ver.5262-01)

Viscosity

- 15W-40

Specifications:

- API SP/CF

Approvals:

- -

Recommendations:

- -

| | PN | Variant |
|------------------------|---------|---------|
| 5262 Family | 5262005 | 5L |
| | 5262020 | 20L |
| | 5262200 | 200L |

Features & Benefits

- Multigrade, high performance engine oil that provides excellent protection against wear, with exceptional oil consumption control properties.
- Protects against formation and corrosion.
- Excellent detergent and dispersant technology.
- Suitable for petrol, light diesel, LPG and E10 fuelled engines.
- 5L, 20L and 200L variants available (Note: Not all variants are available through all Bapcor Business Units).

Typical Characteristics

| Property | Test Method | Value | Unit |
|------------------------------------|-------------|-----------|------|
| Density @ 15 Deg C | DIN 51757 | 0.87 | Kg/L |
| High Temperature High Shear (HTHS) | ASTM D4683 | > 3.7 | - |
| Kinematic Viscosity @ 100 Deg C | ASTM D445 | 14.0 typ. | cSt |
| Viscosity Index | ASTM D2270 | > 130 | - |