

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL ATF D6

Full Synthetic Transmission Oil

January 22, 2025 (Ver.5273-01)

Viscosity

- -

Specifications:

- DEXRON VI
- FORD MERCON LV
- ZF TE-ML 09

Approvals:

- -

Recommendations:

- AISIN WARNER/AW-1
- BMW 81 22 9 400 272/275
- BMW 81 22 9 407 738/858/859
- BMW 83 22 0 397 114
- BMW 83 22 0 403 248/240
- BMW 83 22 0 432 807
- BMW 83 22 2 167 718
- BMW 83 22 2 355 599/601
- FIAT 9.55550-AV2
- GM 9256039/88863400
- HONDA DW-1
- HYUNDAI NWS 9638/SP IV
- KIA SP-IV
- MITSUBISHI ATF-PA/MA1
- NISSAN MATIC S
- TOYOTA TYPE WS
- VW G 055 540 A2
- MAZDA FZ
- ISUZU WSI
- FORD M2C949-A

Features & Benefits

- Full synthetic, premium performance ATF formulated for automatic transmissions of Japanese, European and American manufacturers.
- Increased fuel efficiency.
- 20L and 200L variants available (Note: Not all variants are available through all Bapcor Business Units).

5273 Family	PN	Variant
	5273020	20L
	5273200	200L

Typical Characteristics

Property	Test Method	Value	Unit
Density at 15 °C	DIN 51757	0.851	g/ml
Kinematic Viscosity at 100°C	DIN 51562-1	6	mm ² /s
Kinematic Viscosity at 40°C	DIN 51562-1	29	mm ² /s
Pour Point	DIN ISO 3016	-48	°C
Product dyeing	DIN 10964	red	-
Viscosity Index	DIN ISO 2909	155	-

Superiol.com.au

Superiol.co.nz