

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL ATF MULTI

Full Synthetic Transmission Oil

January 22, 2025 (Ver.5276-01)

Viscosity

- -

Specifications:

- JASO M315 TYPE 1A

Approvals:

- -

Recommendations:

- BMW MINI 83 22 0 402 413
- BMW MINI 83 22 7 542 290
- CHRYSLER MS7176E/9602 (ATF +3/+4)
- DAIHATSU ALUMIX ATF MULTI dexron® III
- FIAT 9.55550-AV1/AV4
- FORD MERCON / M2C924-A / M2C922-A1
- FORD MERCON V
- GM 9986195
- HONDA ATF Z-I
- HYUNDAI SP-III
- ISUZU BESCO ATF-II/ATFIII
- JATCO 3100 PL085/ FWD (N402) / JF506E(K17)
- JWS 3309/TYP E T-IV
- MAZDA ATF D-III/ATF M-3/ATF M-V
- MITSUBISHI SP-II/-III
- NISSAN C/D/J
- SAAB 3309
- SUBARU ATF OIL/ATF OIL SPECIAL/ ATF HP
- SUZUKI ATF 3309/3317
- TOYOTA TYPE D-2
- TOYOTA TYPE T/T-II/T-III/T-IV
- VW G 052 990/055 025

Features & Benefits

- Ultra high-performance ATF specially formulated for Japanese passenger and light commercial vehicles, as well as transmissions used by several European and American manufacturers.
- High torque capacity that exceeds the performance of many original fluids.
- Outstanding ageing and oxidation stability.
- High friction level constant over lifetime.
- 20L and 200L variants available (Note: Not all variants are available through all Bapcor Business Units).

5276 Family	PN	Variant
	5276020	20L
	5276200	200L

Typical Characteristics

Property	Test Method	Value	Unit
Kinematic Viscosity at 40°C	DIN 51562-1	37.3	mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	7.3	mm ² /s
Viscosity Index	DIN ISO 2909	165	-
Density at 15 °C	DIN 51757	0.852	g/ml
Pour Point	DIN ISO 3016	-43	°C

Superiol.com.au

Superiol.co.nz