

SUPERIOL

PRODUCT DATA SHEET



SUPERIOL HYDRAULIC 68

Mineral Hydraulic Oil

January 24, 2025 (Ver.5279-01)

Viscosity

- -

Specifications:

- ISO 68

Approvals:

- -

Recommendations:

- BOSCH REXROTH
- ISO 6743-4: HM
- DIN 51524-2: HLP
- VICKERS VANE PUMP
- DENISON HF-0, HF-1, HF-2
- CINCINNATI MILACRON P-68, P-69, P-70

	PN	Variant
5279 Family	5279020	20L
	5279200	200L
	52791000	1000L (IBC)

Features & Benefits

- Anti-wear hydraulic oil formulated with a blend of high-quality conventional base stocks and Advanced Circular Technologies (ACT).
- Provides improved ageing resistance and protection against corrosion and wear.
- Recommended for use in a wide variety of industrial, mobile, and mining hydraulic system applications.
- 20L, 200L and 1000L (IBC) variants available (Note: Not all variants are available through all Bapcor Business Units).

Typical Characteristics

Property	Test Method	Value	Unit
Kinematic Viscosity @ 40 °C	ASTM D445	68	cSt
Kinematic Viscosity @ 100 °C	ASTM D445	8.7	mm ² /s
Viscosity Index	ASTM D2270	100	-
Density @ 15 °C	DIN 51757	0.868	Kg/L
Flash Point, COC	ASTM D92	>185	°C
Pour Point	ASTM D97	-24	°C