

# SAFETY DATA SHEET

## SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

<b>Product ID:</b>	MSBC20, 20L MSBC5, 5L		
<b>Product Name:</b>	Motospray Brake & Parts Cleaner 20L		
<b>Revision Date:</b>	Jun 06, 2024	<b>Date Printed:</b>	Jun 06, 2024
<b>Version:</b>	1.0	<b>Supersedes Date:</b>	Jan 06, 2023
<b>Manufacturer's Name:</b>	Paragon Filling Pty Ltd	Paragon Filling New Zealand	
<b>Address:</b>	3-5 Hannabus Place Mulgrave, AU, NSW, 2756	21 Highbrook Drive, East Tamaki, Manukau Auckland New Zealand	
<b>Emergency Phone:</b>	13 11 26	0800 764 766	
<b>Information Phone Number:</b>	612 4577-6977	649 250-4635	
<b>Fax:</b>	612 4577-6969		
<b>Product/Recommended Uses:</b>	Brake and parts cleaner		

## SECTION 2) HAZARDS IDENTIFICATION

### Classification

Aspiration Hazard - Category 1  
 Chronic aquatic toxicity - Category 2  
 Flammable Liquids - Category 2  
 Skin Irritation - Category 2  
 Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

### Pictograms



### Signal Word

Danger

### Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways  
 H315 - Causes skin irritation  
 H336 - May cause drowsiness or dizziness

### Hazardous Statements - Physical

H225 - Highly flammable liquid and vapor

### Hazardous Statements - Environmental

H411 - Toxic to aquatic life with long lasting effects

### Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

### Precautionary Statements - Prevention

P241 - Use explosion-proof electrical, ventilating, lighting and all other equipment.

P264 - Wash hands, face and exposed skin thoroughly after handling.

P273 - Avoid release to the environment.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P242 - Use only non-sparking tools.

P243 - Take action to prevent static discharges.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 - Use only outdoors or in a well-ventilated area.

### Precautionary Statements - Response

P312 - Call a POISON CENTER/doctor/physician if you feel unwell.

P321 - Specific treatment- see First Aid on this label.

P378 - Use dry chemical, foam, carbon dioxide to extinguish.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 - Do NOT induce vomiting.

P391 - Collect spillage.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P370 + P378 - In case of fire: Use dry chemical, foam, carbon dioxide to extinguish.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

### Precautionary Statements - Storage

P405 - Store locked up.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P403 + P405 - Store in a well-ventilated place. Store locked up.

### Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local, regional, national and international regulations.

**Acute toxicity of 1.25% of the mixture is unknown**

## SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	>60%
0000064-17-5	ETHYL ALCOHOL	10% - 30%
NA	Ingredients determined not to be hazardous	0% - 10%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## SECTION 4) FIRST-AID MEASURES

### Inhalation

If exposed or concerned: Get medical advice/attention. Remove source of exposure or move person to fresh air, keep comfortable for breathing and keep warm. Call a POISON CENTER/doctor if you feel unwell. Eliminate all ignition sources if safe to do so.

### Eye Contact

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

### Skin Contact

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). If exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. Wash contaminated clothing before re-use or discard. For gross contamination, immediately drench with water and remove clothing. For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

### Ingestion

Rinse mouth. Give a glass of water to drink. Do NOT induce vomiting. If vomiting occurs naturally, give further water. Call a POISON CENTER/doctor if you feel unwell. Never give anything by mouth to an unconscious or convulsing person. IF exposed or concerned: Get medical advice/attention.

### Most Important Symptoms and Effects, Both acute and Delayed

No data available.

### Indication of Any Immediate Medical Attention and Special Treatment Needed

Treat symptomatically.

## SECTION 5) FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Small Fire: Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

Large Fire: Water spray, fog or alcohol-resistant foam.

### Unsuitable Extinguishing Media

Do not use straight stream of water.

### Specific Hazards in Case of Fire

Containers may explode in fire. Cylinders exposed to fire may vent and release toxic gas through pressure relief devices. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Ruptured cylinders may rocket. Electrical requirements for work area should be assessed according to AS3000. Vapors may travel to source of ignition and flash back. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). May form flammable vapour mixtures with air. Highly flammable liquid and vapour. On burning or decomposing may emit toxic fumes.

### Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

### Special Protective Actions

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

## SECTION 6) ACCIDENTAL RELEASE MEASURES

### Emergency Procedure

Isolate hazard area and keep unauthorized personnel away. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Stay uphill and/or upstream. Do not walk through released material.

### Recommended Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

### Personal Precautions

DO NOT breathe vapor or mist.

DO NOT get on skin, eyes or clothing.

### Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Suppress gases with water spray jet. Neutralization may be required before discharging sewage into treatment plants.

### Methods and Materials for Containment and Cleaning up

Ventilate area after clean-up is complete. For small spills: wipe up with absorbent (clean rag or paper towels). For large spills: absorb with vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal. Use clean, non-sparking tools to collect absorbed material. Dispose of contaminated materials according to federal, state and local regulations.

## SECTION 7) HANDLING AND STORAGE

### General

Remove contaminated clothing and protective equipment before entering eating areas.

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

All containers must be properly labelled.

Eyewash stations and showers should be available in areas where this material is used and stored.

DO NOT breathe vapor or mist.

### Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

### Storage Room Requirements

Store gas cylinders separately, away from processing and handling areas, and from incompatible materials. Eliminate all sources of ignition. Protect containers against banging or other physical damage when storing, transferring, or using them. Keep containers securely sealed when not in use, check regularly for leaks. Empty containers retain residue and may be dangerous. Store in dry, well-ventilated, cool areas, out of direct sunlight and away from incompatible materials and other sources of heat.

## SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

### Eye protection

Wear indirect-vent, impact and splash resistant goggles when working with liquids

### Skin Protection

Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity.

### Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to AS/NZS 1715 and AS/NZS 1716 should be followed. Check with respiratory protective equipment suppliers. If risk of inhalation exists wear organic vapor/particulate respirator.

### Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH TWA (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	WES TWA (mg/m3)
ALIPHATIC, LIGHT HYDROCARBON SOLVENT	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			(L)[N159](L)[N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr[N159]URT irr[N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	
ETHYL ALCOHOL		1000			A3	URT irr	A3	1880

Chemical Name	WES STEL (ppm)	WES STEL (mg/m3)	WES TWA (ppm)	WES HEALTH	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)
ALIPHATIC, LIGHT HYDROCARBON SOLVENT					500	2000		
ETHYL ALCOHOL			1000		1000	1900		

Chemical Name	OSHA Skin designation	OSHA Carcinogen
ALIPHATIC, LIGHT HYDROCARBON SOLVENT		
ETHYL ALCOHOL		

A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, irr - Irritation, URT - Upper respiratory tract

**SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES****Physical and Chemical Properties**

Density	6.18 lb/gal
Specific Gravity	0.74
% VOC	98.75%
Density VOC	6.10 lb/gal
% Solids By Weight	1.25%

---

Appearance	Liquid
Odor Description	Characteristic petroleum
Odor Threshold	Data not available
pH	Data not available
Water Solubility	Insoluble
VOC Part A & B Combined	Data not available
Flash Point	-12 °C
Flash Point Symbol	Data not available
Viscosity	Data not available
Lower Explosion Level	Data not available
Upper Explosion Level	Data not available
Vapor Pressure	Data not available
Vapor Density	Data not available
Freezing Point	Data not available
Melting Point	Data not available
Low Boiling Point	Data not available
High Boiling Point	Data not available
Auto Ignition Temp	Data not available
Decomposition Pt	Data not available
Evaporation Rate	Data not available
Coefficient Water/Oil	Data not available

**SECTION 10) STABILITY AND REACTIVITY****Stability**

The product is stable under normal storage conditions.

**Conditions to Avoid**

Elevated temperatures and sources of ignition.

**Hazardous Reactions/Polymerization**

Will not occur.

**Incompatible materials**

Oxidizing agents.

**Hazardous Decomposition Products**

Oxides of carbon and nitrogen, smoke and other toxic fumes.

**SECTION 11) TOXICOLOGICAL INFORMATION****Skin Corrosion/Irritation**

Causes skin irritation

0000064-17-5 ETHYL ALCOHOL

Contact can irritate the skin. Prolonged or repeated exposure can cause drying and cracking of the skin with peeling, redness and itching.

**Carcinogenicity**

No data available.

**Serious Eye Damage/Irritation**

No data available.

**Respiratory/Skin Sensitization**

Material may be an irritant to mucous membranes and respiratory tract.

Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

No data available.

**Germ Cell Mutagenicity**

No data available.

**Reproductive Toxicity**

0000064-17-5 ETHYL ALCOHOL

High concentration may damage the fetus.

**Specific Target Organ Toxicity - Single Exposure**

May cause drowsiness or dizziness

0000064-17-5 ETHYL ALCOHOL

Exposure can cause headache, drowsiness, nausea and vomiting, and unconsciousness. It can also affect concentration and vision.

**Specific Target Organ Toxicity - Repeated Exposure**

May cause damage to organs.

Prolonged exposure to inhalation of high concentration can lead to unconsciousness.

0000064-17-5 ETHYL ALCOHOL

Repeated high exposure may affect the liver and the nervous system. Chronic ingestion of ethanol may cause liver cirrhosis.

**Aspiration Hazard**

May be fatal if swallowed and enters airways

**Acute Toxicity**

Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination and impaired judgment.

Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

0000064-17-5 ETHYL ALCOHOL

Inhalation can irritate the nose, throat and lungs.

**Potential Health Effects - Miscellaneous**

0000064-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

0064742-89-8 ALIPHATIC, LIGHT HYDROCARBON SOLVENT

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

**Likely Routes of Exposure**

0000064-17-5 ETHYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapor or by ingestion.

## SECTION 12) ECOLOGICAL INFORMATION

### Toxicity

Toxic to aquatic life with long lasting effects

0000064-17-5 ETHYL ALCOHOL

S gairdneri: 13.0g/l (96hr LC50) Nauplii : 858 g/l (48hr EC50) Ceriodaphnia dubia : 9.6mg/l (10 day NOEC) Freshwater Fish 250mg/l (NOEC) Reference: REACH registration Dossier.

### Persistence and Degradability

0000064-17-5 ETHYL ALCOHOL

Readily biodegradable. Half-life in air = 38 h

### Bio-accumulative Potential

0000064-17-5 ETHYL ALCOHOL

Substance has a low potential for bioaccumulation (log Kow3),

### Mobility in Soil

No data available.

### Other Adverse Effects

No data available.

## SECTION 13) DISPOSAL CONSIDERATIONS

### Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

## SECTION 14) TRANSPORT INFORMATION

### ADG Information

Packaging Group II

Flammable Liquid Class 3

UN No: 1993

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail".

HAZCHEM: 3YE

Proper Shipping Name: FLAMMABLE LIQUID N.O.S (SOLVENT NAPHTHA)

### IMDG Information

Packaging Group II

Flammable Liquid Class 3

UN No: 1993

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea

This material is classified as a marine Pollutant (P) according to the International Maritime Dangerous Goods Code.

Proper Shipping Name: FLAMMABLE LIQUID N.O.S (SOLVENT NAPHTHA)

### IATA Information

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Proper Shipping Name: FLAMMABLE LIQUID N.O.S (SOLVENT NAPHTHA)

Packaging Group II

Flammable Liquid Class 3





## SECTION 15) REGULATORY INFORMATION

### HSNO Group Standard: Aerosols Flammable Group Standard 2006: HSR002515

HSR002662 – Surface Coatings and Colourants (Flammable) Group Standard 2006

- 3.1C Flammable liquid – medium hazard  
 6.1E Substances that are acutely toxic – May be harmful, aspiration hazard  
 6.3A Substances that are irritating to the skin  
 9.1B Substances that are ecotoxic in the environment

CAS	Chemical Name	% By Weight	Regulation List
0064742-89-8	ALIPHATIC, LIGHT HYDROCARBON SOLVENT	>60%	DSL,VOC,IARCCarcinogen,TSCA
0000064-17-5	ETHYL ALCOHOL	10% - 30%	DSL,VOC,IARCCarcinogen,TSCA

## SECTION 16) OTHER INFORMATION INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

### Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ADG- Australian Dangerous Goods Code; CAS- Chemical Abstract Service; DSL- Domestic Substances List; LC- Lethal Concentration; LD- Lethal Dose; OSHA- Occupational Safety and Health Administration; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; VOC- Volatile Organic Compounds; WES- Workplace Exposure Standards

### Version 1.0:

Revision Date: Jun 06, 2023

First Edition.

## DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.