

1. Identification of Substance & Company

Product name Radtech RX300 Antifreeze

Other namesNAProduct codeRTRX300HSNO approvalHSR002606

Approval description Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents

(Subsidiary Hazard) Group Standard 2020

UN number NA
DG class NA
Proper Shipping Name NA
Packaging group NA
Hazchem code NA

Uses Antifreeze/Antiboil

Company Details

Company Fargo International Ltd Address 71F Adams drive.

Auckland. New Zealand

Telephone +64 9 238 2389 [8.00 - 4.30 Mon to Fri]

Fax +64 9 238 2399

Emergency Telephone Number: +64 21 930 795 (24 hours emergency only)
National Poison Centre NZ (24 hours): 0800 POISON [764 766]

2. Hazard Identification

Approval

This product has been approved under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002606, Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2020). The substance has been classified as hazardous according to the criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

GHS 7 Classes Hazard Statements

Eye irritation cat 2 H320 - Causes eye irritation.

STOT RE cat 1 H372 - Causes damage to organs through prolonged or repeated exposure.

SYMBOLS

DANGER





HSNO Classes Hazard Statements

6.4A H320 - Causes eye irritation.

6.9A H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

P260 - Do not breathe vapours.

P264 - Wash hands thoroughly after handling.



P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

P280 - Wear eye protection.

P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P301+P312 - IF SWALLOWED: Call a POISON CENTRE or doctor/physician if you feel unwell.

P330 - Rinse mouth.

P308+P313 - IF exposed or concerned: Get medical advice/ attention.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
Ethylene glycol	107-21-1	60%
Ingredients not contributing to HSNO classes	mixture	balance

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been harmed or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service). IF exposed or concerned: Get medical advice/ attention.

Recommended first aid

facilities

Ready access to running water is recommended.

Exposure

Swallowed Do NOT induce vomiting. Give a glass of water to drink. Call a POISON CENTRE or

doctor/physician if you feel unwell.

Eye contact If product gets in eyes, wash material from them with running water for several minutes.

If eye irritation persists: Get medical advice/attention.

Skin contact

Inhaled

This product is non-irritating to skin. No further measures should be required. Generally, inhalation of vapours is unlikely to result in adverse health effects. If

coughing, dizziness or shortness of breath is experienced, remove the patient to fresh air immediately. If patient is unconscious, place in the recovery position (on the side) for

transport and contact a doctor.

Advice to Doctor

Treat symptomatically

5. Firefighting Measures

Fire and explosion hazards: Suitable extinguishing

There are no specific risks for fire/explosion for this chemical. It is non-flammable. Carbon dioxide, extinguishing powder or water jet. Fight larger fires with water jet or

Unsuitable extinguishing

substances:

substances:

alcohol resistant foam. Unknown.

Products of combustion:

Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water.

Product Name: Radtech RX300 Antifreeze

May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying

spaces, forming potentially explosive mixtures.

Protective equipment: Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat

and eye protection.

Hazchem code: NA



6. Accidental Release Measures

Containment If greater than 10000L is stored, secondary containment and emergency plans to

manage any potential spills must be in place. In all cases design storage to prevent

discharge to stormwater.

Emergency procedures In the event of spillage alert the fire brigade to location and give brief description of

hazard. Stop the source of the leak, if safe to do so. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Do not use sawdust on concentrate. Prevent by whatever means possible any spillage from entering drains, sewers, or water courses. (If

this occurs contact your regional council immediately).

clean-up of spills, as they may create fire or environmental hazard. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or

waterways has occurred advise local emergency services.

Disposal Mop up and collect recoverable material into labelled containers for recycling or salvage.

Recycle containers wherever possible. This material may be suitable for approved

landfill. Dispose of only in accord with all regulations.

Precautions Spill may be a slip hazard. Wear protective equipment to prevent skin and eye

contamination and the inhalation of vapours. Work up wind or increase ventilation.

7. Storage & Handling

Storage Avoid storage of harmful substances with food. Store out of reach of children.

Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. Avoid contact with incompatible substances as listed in

Section 10.

Handling Keep exposure to a minimum, and minimise the quantities kept in work areas. See

section 8 with regard to personal protective equipment requirements. Avoid eye contact

and inhalation of vapour, mist or aerosols.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace Ingredient WES-TWA* WES-STEL Exposure Stds Ethylene glycol ceiling: 50ppm (127mg/m³) data unavailable

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Eyes



Avoid contact with eyes. Use safety glasses and or chemical splash goggles if splashes are possible. Select eye protection in accordance with AS/NZS 1337.

Skin

Avoid repeated or prolonged skin contact. If discomfort is felt (e.g., if pre-existing conditions exist, such as dermatitis, cuts or sensitive skin), gloves may be helpful. If you suffer from dermatitis type skin conditions, use gloves. PVC, nitrile rubber gloves are recommended. Protective gloves or suitably resistant material must comply with AS 2161. Replace frequently. Gloves should be checked for tears or holes before use. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking.

Product Name: Radtech RX300 Antifreeze



Respiratory A respirator when airborne concentrations approach the WES (section 8). Respirators

must have filters appropriate to the duty and comply with AS/NZS1716 and selected, used and maintained in accordance with AS/NS 1715. Use a respirator with an organic vapour cartridge. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order. Fit testing and clear guidelines

and training for use and maintenance of PPE are necessary.

WES Additional Information

Not applicable

9. Physical & Chemical Properties

Appearancegreen liquidOdourslight odour

pH 7.5-8.5 (1% in water) **Vapour pressure** 0.12 mmHg@20°C

Viscosity no data
Boiling point 130°C
Volatile materials no data
Freezing / melting point -27°C

Solubility miscible in water and alcohols

Specific gravity / density 1.05 - 1.06 at 20°C

Flash point no data
Danger of explosion not explosive
Auto-ignition temperature no data
Upper & lower flammable limits
Corrosiveness non corrosive

10. Stability & Reactivity

Stability Stable

Conditions to be avoided Containers should be kept closed in order to avoid contamination. Keep from extreme

heat and open flames.

Incompatible groups Strong acids, strong bases, oxidising agents.

Substance Specific

Incompatibility

none known

Hazardous decomposition

products

Hazardous reactions none known

11. Toxicological Information

Summary

IF SWALLOWED: Ingestion may cause gastrointestinal irritation, inebriation, drowsiness, nausea, vomiting and diarrhoea. May cause central nervous system depression.

IF IN EYES: may cause eye irritation.

IF ON SKIN: no effect expected.

IF INHALED: Inhalation of high concentration of vapours may cause respiratory irritation and affect the central nervous system. Symptoms include dizziness, drowsiness, headaches and inebriation and possible loss of consciousness. CHRONIC TOXICITY: Long term exposure to ethylene glycol may affect the kidneys, CNS and metabolism.

Supporting Data

Acute Oral Using LD_{50} 's for ingredients, the calculated LD_{50} (oral, rat) for the mixture is >2000mg/kg.

Data considered includes: ethylene glycol LD₅₀ (oral): 1670 mg/kg bw (cat), 5500mg/kg

(dog), 6610mg/kg (guinea pig).

Dermal Using LD₅₀'s for ingredients, the calculated LD₅₀ (dermal, rat) for the mixture is >5000

mg/kg. Data considered includes: ethylene glycol LD50 (dermal): 9.53mL/kg (rabbit).

Oxides of carbon, some toxic fumes may be emitted during thermal decomposition.

Inhaled No evidence of inhalation toxicity.

Eye The mixture is considered to be an eye irritant. Ethylene glycol is an eye irritant.

Skin The mixture is not considered to be a skin irritant.

Product Name: Radtech RX300 Antifreeze



Chronic Sensitisation No ingredient present at concentrations > 0.1% is considered a sensitizer.

> Mutagenicity No ingredient present at concentrations > 0.1% is considered a mutagen. Carcinogenicity No ingredient present at concentrations > 0.1% is considered a carcinogen. Reproductive / No ingredient present at concentrations > 0.1% is considered a reproductive or

Developmental developmental toxicant or have any effects on or via lactation.

Systemic Ethylene glycol is a known systemic toxicant. Long term exposure may affect the kidneys,

CNS and metabolism.

None known.

Aggravation of

existing conditions

12. Ecological Data

Summary

This mixture is not considered to be ecotoxic towards aquatic organisms, but is harmful towards terrestrial vertebrates.

Supporting Data

Aquatic Using EC₅₀'s for ingredients, the calculated EC₅₀ for the mixture is > 100 mg/L. Data

considered includes: ethylene glycol >100mg/L

Bioaccumulation No data Degradability No data Soil No data

Terrestrial vertebrate The mixture is classed 9.3C. Using LD_{50} 's for ingredients, the calculated LD_{50} (oral, rat)

for the mixture is between 500 and 2,000 mg/kg. Data considered includes: ethylene glycol LD₅₀ (oral): 1670 mg/kg bw (cat), 5500mg/kg (dog), 6610mg/kg (guinea pig).

Terrestrial invertebrate No evidence of toxicity towards terrestrial invertebrates.

Biocidal

Environmental effect levels No EELs are available for this mixture or ingredients

13. Disposal Considerations

Restrictions There are no product-specific restrictions, however, local council and resource consent

conditions may apply, including requirements of trade waste consents.

Disposal method Disposal of this product must comply with the Hazardous Substances (Disposal) Notice

2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore

rendered non-hazardous before discharge to the environment.

Contaminated packaging Disposal of contaminated packaging must comply with the Hazardous Substances

(Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible

reuse or recycle packaging.

14. Transport Information

There are no specific restrictions for this product (not a dangerous good).

UN number: NA Proper shipping name: NA Class(es) NA Packing group: NA **Precautions:** NA Hazchem code: NA



15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002606, Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2020. All ingredients appear on the NZIoC.

Specific Workplace Controls (as per HSNO approval referenced to Controls Matrix)

Key workplace requirements are:

SDS To be available within 10 minutes in workplaces storing any quantity.

Inventory An inventory of all hazardous substances must be prepared and maintained.

Packaging All hazardous substances should be appropriately packaged including substances

that have been decanted, transferred or manufactured for own use or have been

supplied

Labelling Must comply with the Hazardous Substances (Labelling) Notice 2017.

Emergency plan Required if > 10000L is stored.

Certified handler Not required.

Tracking Not required.

Bunding & secondary containment Required if > 10000L is stored.

Signage Not required.

Location compliance certificate Not required.

Flammable zone Not required.

Fire extinguisher Not required.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information

Abbreviations

Approval Code Approval HSR002606, Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents

(Subsidiary Hazard) Group Standard 2020 Controls, EPA. www.epa.govt.nz

CAS Number Unique Chemical Abstracts Service Registry Number

EC50 Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test

population (e.g. daphnia, fish species)

EPA Environmental Protection Authority (New Zealand)

Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised

edition, 2017, published by the United Nations.

HAZCHEM Code Emergency action code of numbers and letters that provide information to emergency

services, especially fire fighters

HSNO Hazardous Substances and New Organisms (Act and Regulations)

International Agency for Research on Cancer

LEL Lower Explosive Limit

LD₅₀ Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).

LC₅₀ Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population

(usually rats)

NZIoC New Zealand Inventory of Chemicals

MSDS (SDS) Material Safety Data Sheet (or Safety Data Sheet)

STEL Short Term Exposure Limit - The maximum airborne concentration of a chemical or

biological agent to which a worker may be exposed in any 15 minute period, provided the

TWA is not exceeded

STOT RESystem Target Organ Toxicity – Repeated Exposure **STOT SE**System Target Organ Toxicity – Single Exposure

TWA Time Weighted Average – generally referred to WES averaged over typical work day

(usually 8 hours)

UEL Ùpper Explosive Limit



Product Name: Radtech RX300 Antifreeze

UN Number United Nations Number

WES Workplace Exposure Standard - The airborne concentration of a biological or chemical

agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring

using procedures that gather air samples in the worker's breathing zone.

References

Unless otherwise stated comes from the EPA HSNO chemical classification information

database (CCID).

Controls EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances)

Regulations 2017, www.legislation.govt.nz

WES The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available

on their web site – www.worksafe.govt.nz.

Other References: EU ECHA, ingredients SDS's, ChemIDplus

Review

DateReason for reviewSeptember 2021Not applicable – new SDS

Disclaimer

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for and loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.