



SAFETY DATA SHEET

According to
HSNO Hazardous Substances (Safety Data Sheets) Notice 2017

Section 1: Identification of the Substance/Mixture and of the Supplier

Product: **Super Solve**
Product Use: Industrial Chemical Cleaner
Restriction of Use: Refer to Section 15

Company Details: **Marketing Chemicals Ltd**
Address: 2 Rymer Place, Mangere Bridge
Auckland, New Zealand

Telephone: +64 9 634 3862 [8.00 am to 4.30pm – Monday to Friday]
Fax: +64 9 634 3864

Emergency No: **+64 274 340 990(24 hours)**
0800 764 766 (National Poison Centre)

Date of SDS Preparation: 6 September 2019

Section 2: Hazard Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval No: **Solvents (Flammable) - HSR0002662**

Pictograms:



Flammable



Chronic



Ecotoxic

Signal Word: **DANGER**

HSNO Classes	Hazard Code	Hazard Statement	GHS Category
3.1C	H226	Flammable liquid and vapour.	Flam. Liq. 3
6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Asp. Tox. 1
6.1E (resp)	H335	May cause respiratory irritation.	STOT SE 3
6.3B	H316	Causes mild skin irritation.	Skin Irrit. 3
6.4A	H319	Causes serious eye irritation.	Eye Irrit. 2A
6.8B	H361	Suspected of damaging fertility or the unborn child	Repr. 2
6.9A	H372	Causes damage to organs through prolonged or repeated exposure.	STOT RE 1
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.

Product Name: Super Solve
Date of SDS: 6 September 2019

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe fumes.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective clothing as detailed in Section 8.
P281	Use personal protective equipment as required.

Response code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use CO2, Dry Chemical or Foam, Water spray or Fog for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Refer to Section 13.

Section 3: Composition/Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Aliphatic hydrocarbon, low aromatic	48 – 52	64742-82-1
Detergents & Wetting Agents	20-25	9016-45-9
Aromatic hydrocarbon* * That may contain	28 – 32	64742-95-6
1,2,4-Trimethylbenzene	<16	95-63-6
Mesitylene	<6	108-67-8
Propylbenzene and Isopropylbenzene (Cumene),	<3	
Xylene, mixed isomers	<1	1330-20-7

Section 4: First Aid Measures

Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If on Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Get medical attention if irritation persists.

If Swallowed	Rinse mouth. Do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Call a POISON CENTER or doctor/physician if you feel unwell.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion	May be fatal if swallowed and enters airways.
Inhalation	May cause respiratory irritation.
Skin	Causes mild skin irritation.
Eyes	Causes serious eye irritation.
Chronic	Suspected of causing genetic defects. Causes damage to organs through prolonged or repeated exposure.
Notes to Physician	Treat according to symptoms. Gastric lavage may be indicated if ingested but protect airway as risk of aspiration into lungs with potential to cause chemical pneumonitis. Do not wait for symptoms to develop. General measures should be taken to control acidosis and maintain urine output.

Section 5: Fire Fighting Measures

Hazard Type	Flammable Liquid or vapour
Flash Point	41°C
Auto Ignition Point	>200°C
Flammable Limits in Air % by Volume	Not available
Hazards from combustion products	None known
Suitable Extinguishing media	Foam or water fog. Dry chemical, carbon dioxide, sand and earth are suitable for extinguishing small fires.
Precautions for firefighters and special protective clothing	Proper respiratory equipment to protect against the hazardous effects of combustion products is recommended. Water in a straight hose stream may cause fire to spread and should be used as a cooling medium only. Vapour accumulations may flash and/or explode if ignited. Keep ignition sources, open flames, ect. away from those fumes.
HAZCHEM CODE	3Y

Section 6: Accidental Release Measures

SMALL SPILL: Extinguish possible sources of ignition. Evacuate all unprotected personnel and ventilate area. Only personnel equipped with proper respiratory, skin/eye protection should enter spill area. Dike area to contain spill and clean up by absorbing on an inert absorbent or other means. Don't flush into sewers or natural waterways.

LARGE SPILL: Contain material as described above and call the local fire or police department for immediate emergency assistance.

Section 7: Handling and Storage

PROCEDURE FOR HANDLING

- Read label before use.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames and hot surfaces. No smoking.

- Open container slowly to relieve any pressure
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical, ventilating, and lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe fumes or vapours.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Avoid release to the environment.
- Wear protective clothing.
- Use personal protective equipment as required.

STORAGE REQUIREMENTS

- Store in a well-ventilated place. Keep cool and dry.
- Store locked up.
- Keep container tightly closed.
- Store away from incompatible materials listed in Section 10.

Section 8: Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance		TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Xylene	[1330-20-7]	50	217	-	-

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

Personal Protection Equipment



- Engineering Controls:** General (mechanical) room ventilation is considered satisfactory in enclosed spaces. Where explosive mixtures may be present, electrical systems safe for such locations must be used.
- Eye / Face Protection:** Wear safety glasses with side shields or goggles when handling this material.
- Body Protection:** PVC-coated gloves. Avoid skin contact. If skin contact or contamination of clothing is likely, protective clothing should be worn.
- Respiratory Protection:** Use NIOSH/MSHA approved respirators. Where concentrations in air may exceed the limits described in the National Exposure Standards, it is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type “A” filter material is considered suitable for this product.

Section 9: Physical and Chemical Properties

Appearance	Liquid
Colour	Clear Colourless
Odour	Not available
Odour Threshold	Not available
pH	Not applicable
Boiling Point	154-192°C

Melting Point	Not available
Freezing Point	Not available
Flash Point	41°C
Flammability	Flammable
Upper and Lower Explosive Limits	Not available
Vapour Pressure	Not available
Vapour Density	Not available
Specific Gravity	Not available
Solubility in Water	Insoluble
Partition Coefficient:	Not available
Auto-ignition Temperature	>200°C
Decomposition Temperature	Not available
Kinematic Viscosity	Not available
Particle Characteristics	Not applicable
Evaporation Rate	Not available
% Volatiles	100

Section 10: Stability and Reactivity

Stability of the Substance:	Stable under normal storage and use conditions.
Conditions to avoid:	Exposure to excessive heat, open flames and sparks. Avoid conditions that favour the formation of excessive mists and/or fumes.
Materials to avoid:	Strong oxidising agents
Hazardous Decomposition Products:	None known
Conditions Contributing to Hazardous Polymerization	Not known.

Section 11: Toxicological Information

Acute Effects:

Swallowed	Not triggered, however if ingesting any amount of this product will result in headaches, nausea, dizziness, and tracheal burning.
Dermal	Not applicable.
Inhalation	Not triggered however, this product may be irritating if inhaled resulting in coughing, wheezing, choking, or breathing difficulties. Exposure to large concentrations over an extended period will result in central nervous system (CNS) depression with symptoms of headache, nausea, and lack of co-ordination.
Eye	This product is irritating to eyes, but will not permanently damage the eye tissue.
Skin	This product is irritating to the skin with prolonged exposure. It may result in dryness and cracking. Prolonged or repeated exposure may lead to dermatitis.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Suspected of causing genetic defects.
Aspiration	May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the lungs during ingestion, or from vomiting, may cause chemical pneumonitis, or pulmonary oedema
STOT/SE	Not applicable.
STOT/RE	Causes damage to organs through prolonged or repeated exposure.

Individual component information:

Product Name: Super Solve
Date of SDS: 6 September 2019

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Acute Toxicity:

Chemical Name	Oral – LD50	Dermal – LD50	Inhalation – LC50
1,2,4-Trimethylbenzene (Cas no 95-63-6)	3280mg/kg (rat)	-	18 mg/L(Rat) 4hr
Xylene (Cas No 1330-20-7)	1590mg/kg (Mouse)	-	27.6mg/L (rat)

Section 12: Ecotoxicological Information

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

Environmental Precautions: Do not allow product to wash into waterways.

Persistence and degradability	Expected to be biodegradable
Bioaccumulation	not bio accumulative
Mobility in Soil	No data available
Other adverse effects	Oxidized rapidly by photochemical reactions in air.

Section 13: Disposal Considerations

Disposal Method:

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national and local authorities. Packaging may still contain fumes and vapours that are flammable and harmful. Ensure that empty packaging is allowed to dry.

This product is NOT suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. This product is ashless and can be burned directly in appropriate equipment.

Precautions or methods to avoid: Do not allow to enter waterways.

Section 14: Transport Information

This product is classified as a **Dangerous Good for transport in NZ ; NZS 5433:2012**

**Road, Rail, Sea and Air Transport**

UN No	1300
Class - Primary	3
Packing Group	III
Proper Shipping Name	TURPENTINE SUBSTITUTE
Marine Pollutant	Yes
Special Provisions	If the product's individual container is below 5L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.
Hazchem Code	3Y

Section 15: Regulatory Information

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Solvents (Flammable) - HSR002662

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500L(>5L), 1500L(<5L)< 250L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L (3.1C)
Emergency Response Plan	1000L (9.1B)
Secondary Containment	1000L(9.1B)
Restriction of Use	None known

Section 16: Other Information

Glossary

EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

Marketing Chemicals Ltd has taken care in compiling this information. No liability is accepted directly or indirectly from its application as conditions of use are outside the Company's control. End users are obliged to conform to relevant Local Government regulations.

For General Information : Marketing Chemicals Ltd,

Phone: +64 (09) 634 3862 / +64 (0)274 340 990

Fax : +64 (09) 634 3864

Issue Date: 6 September 2019

Review Date: 6 September 2024